



# ST 900FC “VanGuard™” Series Straight Cutting Torches



**ST 900FC**

## ST 900FC “Vanguard™” Series

- For use with any fuel gas, 5 PSIG and above.
- Use with **Series 1** Cutting Tips.
- Cutting capacity 1/8"/3.25mm to 6"/152mm.
- Hose connections are 9/16"-18' unless noted.
- **Includes built-in patented flashback arrestors and reverse flow check valves for added safety.**

### ST 900FC “VANGUARD” SERIES ORDERING INFORMATION

Part Number	Model Number	Lever Position	Tip Series	Head Angle	Length
0381-1620	SST 900FC	Top Rear	1	90°	17"/43cm
0381-1622	SST 901FC	Top Rear	1	75°	17"/43cm
0381-1621	ST 900FC	Top Rear	1	90°	21"/53cm
0381-1623	ST 901FC	Top Rear	1	75°	21"/53cm
0381-1628	ST912FC	Top Rear	1	180°	27"/68cm
0381-1624	ST 930FC	Top Rear	1	90°	36"/91cm
0381-1625	ST 931FC	Top Rear	1	75°	36"/91cm
0381-1626	ST 932FC	Top Rear	1	180°	36"/91cm
0381-1629	ST 950FC	Top Rear	1	90°	48"/122cm
0381-1630	ST 951FC	Top Rear	1	75°	48"/122cm



Patent # 5407348


**Outfits with “FC” Models VanGuard™ Series:**

Cutter® “Select™”

*See Outfits Section F*

### A NEW DIMENSION IN OPERATOR SAFETY!

Victor Torch Handles are available with VanGuard™ safety features:



- Built-In Flashback Arrestors  
no need for accessory flash arrestors
- Built-in Reverse Flow Check Valves
- Works with all fuel gases.  
There are pressure restrictions for different gases. VanGuard™ Torch Handles also feature Victor traditional threaded assemblies for quick economical repair if service is necessary.

*\* See page 107, Section E for additional details on flashback arrestors and check valves.*

For tip selection see:

**Tip/Apparatus Users Guide** Section D, pages 90-93.

For **Design and Construction Features** Section C, page 74.